

Metal Roof Sealant



Adheres To

- Lap Joints
- Pipe Boots
- Trim
- Copper*
- Metal Siding
- Metal Roof
- PVC
- Snow Guards
- Single-Ply
- Gutters
- Aluminum
- Stucco
- Roof Flashing
- Downspouts
- Roof Tile
- Termination Bars

Product Advantages

- Adheres to Kynar® coated metals**
- Excellent adhesion and flexibility
- VOC Compliant
- Mildew Resistant
- Application Temperature -20°F to +120°F
- Freeze thaw stable
- Service Temperature -40° F to +400° F
- Invisible to UV light
- Tack free in 10 minutes
- Completely cured in up to 2 days



White
MR100



Blue White
MR101



Antique White
MR105



Black
MR110



Light Gray
MR115



Dark Bronze
MR120



Lincoln Bronze
MR121



Charcoal Gray
MR126



Chocolate Brown
MR131



Medium Bronze
MR134




Brown
MR137



Translucent
MR150



Champagne
MR155



Silver
MR156



Copper
MR157



Hartford Green
MR168



Green
MR169




Regal Blue
MR171***



Brandywine
MR180



Red
MR182



Terracotta
MR184



Sandstone
MR191



Exterior Bronze
MR194



Electric Blue
MR195***




Regal Red
MR196***



Patina Green
MR197



Sierra Tan
MR3333



Almond
MR3461



Gutter Gray
MR3514



Hemlock Green
MR3702



Pacific Blue
MR3801



Silver Metallic
MR4103



Coppertone
MR3201



Gunmetal Gray
MR117



Stone White
MR102



Slate Gray
MR118

* In exposed areas only

** Kynar is a registered trademark of Arkema Inc

*** Bright Color Pricing

Metal Roof Sealant

Technical Information

Product: Novaflex
Metal Roof Sealant

Appearance: Smooth paste

Service Temperature:
-40°F to +400°F

Adhesion: Excellent to most
common building materials

Consistency: Non-sag

Gunning Extrusion: Easy to gun

Flexibility: Good

Water Resistance: Good
– Not to be submerged

Exterior Weathering: Excellent

Aging: Excellent

Freeze-Thaw Stable: Will not freeze

Odor: None

Skin Time:
• 40°F/40% relative
humidity – 40 minutes
• 75°F/50% relative
humidity – 10 minutes
• 95°F/95% relative
humidity – 5 minutes

Through Time:
• 40°F/60% relative
humidity – 2-3 days
• 75°F/50% relative
humidity – < 24 hrs

Weight per gallon: 10.2 pounds

Solids: 97%

Novaflex[®] Metal Roof Sealant provides unbeatable adhesion to metal, coated metals, wood, masonry, PVC and most common construction materials.

Product Specs

Coverage: 1/4" bead application - 28 linear feet

Specifications: Meets or exceeds ASTM C-920, TT-S-001543A and TT-S-230C

Shelf life: Use product within 18 months from manufacturer's date. FREEZE THAW STABLE.

User Tips: Not designed for continuous submersion or use below the waterline.

Clean Up: Clean tools with toluene or mineral spirits before it dries. After setting, excess sealant must be cut or scraped away. Follow solvents vendor's precautions.

Not Recommended For

- Surface temperature below 0°F or exceeding 120°F during installation
- Surfaces continuously immersed in water
- Building materials that bleed oils, plasticizers or solvents that may affect adhesion
- Frost-laden or wet surfaces
- Completely confined joints or if the sealant is intended to be painted

Limited Warranty: Satisfaction guaranteed when handled and applied according to label instructions. Call 1-800-380-0138 for Customer Service.

CAUTION!: Avoid contact with eyes and skin. Wash hands after using.

KEEP OUT OF REACH OF CHILDREN

First Aid: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately.

WARNING: Eye and skin irritant! Do not swallow. Do not allow eye contact or prolonged skin contact.

SEEK IMMEDIATE MEDICAL ATTENTION. Additional information please refer to MSDS.

Disposal: For disposal of material follow federal, state and local regulations.

Product Information

- Description - Metal Roof Sealant
- Item Number - 02-MR0XXX0-10C1
- Size - 10.3 FL. OZ (304 mL)
- Unit Dimensions - 9" x 2" x 2"

Also available in sausage packages:

Item Number - 02-MX0XXXX-20S1

Size - 20 FL Oz

Dimensions - 12 3/4" x 2" (unit)

13 1/2" x 8 1/4" x 6" (case)

Case Pack Information

- Description - Metal Roof Sealant
- Item Number - 02-MR0XXX0-10C1
- Dimensions - 11 15/16" x 9 15/16" x 8 1/8"
- Case Weight 10 lbs. / Cases Per Pallet -120

NOVAGARD
Solutions.
Engineered Products... Innovative Thinking

5109 Hamilton Ave.
Cleveland, OH 44114
1-800-380-0138
www.novagardsolutions.com
Made in USA. For commercial use.

